



DS3D

Doubling the Performance of the Most Powerful Dual Microinverter series

- 2 input channels with independent MPPT and monitoring function
- Single unit connects to 4 modules
- Maximum continuous output power up to 2000VA
- Engineered to match the highest power modules available (Max input current 20A)
- Encrypted ZigBee Communication
- Safety protection relay integrated


PRODUCT FEATURES

APsystems expands its 3rd generation of dual microinverter series with the DS3D. With unprecedented power outputs of 2000VA, the DS3D connects to 4 high power modules (2 by 2 in series). With 2 independent MPPTs, encrypted ZigBee signal, the DS3D benefits from an entirely new architecture.

The innovative design makes the product unique while maximizing power production. The components are encapsulated with silicone to reduce stress on the electronics, facilitate thermal dissipation, enhance waterproof properties and ensure maximum reliability of the system via rigorous testing methods including accelerated life testing. A 24/7 energy access through apps or web-based portal facilitate remote diagnosis and maintenance.

In addition, it provides 97% peak efficiency. DS3D is a game changer for multi residential and commercial PV rooftops.

WIRING SCHEMATIC



Datasheet | DS3D Microinverter

Model	DS3D
Region	LATAM

Input Data (DC)

Recommended PV Module Power (STC) Range	315Wp-670Wp+
Peak Power Tracking Voltage	56V-90V
Operating Voltage Range	52V-120V
Maximum Input Voltage	120V
Maximum Input Current	20A x 2
Maximum input short circuit current	25A per input

Output Data (AC)

Maximum Continuous Output Power	2000VA
Nominal Output Voltage/Range ⁽¹⁾	240V/211V-264V
Adjustable Output Voltage Range	170V-278V
Nominal Output Current	8.3A
Nominal Output Frequency/ Range ⁽¹⁾	60Hz/59.3Hz-60.5Hz
Adjustable Output Frequency Range	55Hz-65Hz
Maximum Units per 10AWG Branch ⁽²⁾	4
Maximum Units per 12AWG Branch ⁽²⁾	3

Efficiency

Peak Efficiency	97%
Nominal MPPT Efficiency	99.5%
Night Power Consumption	20mW

Mechanical Data

Operating Ambient Temperature Range ⁽³⁾	-40 °F to +149 °F (-40 °C to +65 °C)
Storage Temperature Range	-40 °F to +185 °F (-40 °C to +85 °C)
Dimensions (W x H x D)	11" x 9" x 2" (284mm X 234mm X 50.2mm)
Weight	9.5lbs (4.3kg)
AC Bus Cable	10AWG(35A) / 12AWG(28A)
DC Connector Type	Stäubli MC4 PV-ADBP4-S2&ADSP4-S2
Cooling	Natural Convection - No Fans
Enclosure Environmental Rating	Type 6

Features

Communication (Inverter To ECU) ⁽⁴⁾	Encrypted ZigBee
Isolation Design	High Frequency Transformers, Galvanically Isolated
Energy Management	Energy Management Analysis (EMA) system
Warranty ⁽⁵⁾	10 Years Standard

Compliance

Compliance	UL1741 (IEEE1547); CSA C22.2 No. 107.1-16; NOM-001; UL1699B
------------	---

(1) Nominal voltage/frequency range can be extended beyond nominal if required by the utility.

(2) Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

(3) The inverter may enter to power de-grade mode under poor ventilation and heat dissipation installation environment.

(4) Recommend no more than 80 inverters register to one ECU for stable communication.

(5) To be eligible for the warranty, APsystems microinverters need to be monitored via the EMA portal.

Please refer to our warranty T&Cs available on latam.APsistemas.com.

© All Rights Reserved

Specifications subject to change without notice please ensure you are using the most recent update found at web : latam.APsistemas.com.

APsystems en Guadalajara:

AV. Lazaro Cardenas 2850-5o Piso, Colonia Jardines del Bosque C.P.

44520, Guadalajara, Jalisco

+52 (33) 3188 4604 | info.latam@apsistemas.com