

## QT2D

### Doubling the performance of the most powerful 3-phase Quad microinverter

- Designed for 3-phase grid connection
- 4 input channels
- Single unit connects to 8 modules
- Maximum continuous AC output power 3600W
- Engineered to match the highest power modules available (Maximum input current 20A)
- Safety protection relay integrated
- Adjustable output power factor
- Balancing 3-phase output


## PRODUCT FEATURES

APsystems 2<sup>nd</sup> generation of native 3-phase microinverters are reaching unprecedented power outputs of 3600W. Connecting up to 8 high power modules (4 by 2 in series), the QT2D provides a cost-efficient solution ideal for today's fast growing commercial PV segment.

The innovative design makes the product unique while maximizing power production. The components are encapsulated with silicone to reduce stress on the electronics, facilitate thermal dissipation, enhance waterproof properties and ensure maximum reliability of the system via rigorous testing methods including accelerated life testing. A 24/7 energy access through apps or web-based portal facilitate remote diagnosis and maintenance.

The new QT2D is interactive with power grids through a feature referred to as RPC (Reactive Power Control) to better manage photovoltaic power spikes in the grid. In addition, it provides 97% peak efficiency with 20% less components compared to the last generation product. QT2D is a game changer in 3-phase installations for commercial PV rooftops.

## WIRING SCHEMATIC



# Datasheet | QT2D 3-Phase Microinverter

Model	QT2D
Region	BRAZIL

## Input Data (DC)

Recommended PV Module Power (STC) Range	315Wp-670Wp+
Peak Power Tracking Voltage	64V-90V
Operating Voltage Range	52V-120V
Maximum Input Voltage	120V
Maximum Input Current	20A x 4

## Output Data (AC)

Maximum Continuous Output Power	3600W
Nominal Output Voltage/Range <sup>(1)</sup>	380V/304V-418V
Adjustable Output Voltage Range	304V-450V
Nominal Output Current	5.45Ax3
Nominal Output Frequency/ Range <sup>(1)</sup>	60Hz/57.5-62Hz
Adjustable Output Frequency Range	55Hz-65Hz
Maximum Units per 4mm <sup>2</sup> Branch <sup>(2)</sup>	5

## Efficiency

Peak Efficiency	97%
Nominal MPPT Efficiency	99.9%
Night Power Consumption	40mW

## Mechanical Data

Operating Ambient Temperature Range <sup>(3)</sup>	- 40 °C to + 65 °C
Storage Temperature Range	- 40 °C to + 85 °C
Dimensions (W x H x D)	359mm X 273mm X 56mm
Weight	7kg
AC Bus Cable	4mm <sup>2</sup> (28A)
DC Connector Type	Stäubli MC4 PV-ADBP4-S2&ADSP4-S2
Cooling	Natural Convection - No Fans
Enclosure Environmental Rating	IP67

## Features

Communication (Inverter To ECU) <sup>(4)</sup>	Encrypted ZigBee
Isolation Design	High Frequency Transformers, Galvanically Isolated
Energy Management	Energy Management Analysis (EMA) system
Warranty <sup>(5)</sup>	15 Years Standard ; 25 Years Optional

## Compliances

Safety, EMC & Grid Compliances	ABNT NBR 16149:2013; ABNT NBR 16150:2013; ABNT NBR IEC 62116:2012
--------------------------------	--

(1) Nominal voltage/frequency range can be extended beyond nominal if required by the utility.

(2) Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

(3) The inverter may enter to power de-grade mode under poor ventilation and heat dissipation installation environment.

(4) Recommend no more than 80 inverters register to one ECU for stable communication.

(5) To be eligible for the warranty, APsystems microinverters need to be monitored via the EMA portal. Please refer to our warranty T&Cs available on [latam.apsystems.com](http://latam.apsystems.com).

© All Rights Reserved

Specifications subject to change without notice please ensure you are using the most recent update found at web : [latam.apsystems.com](http://latam.apsystems.com)

## APsystems en Guadalajara:

AV. Lazaro Cardenas 2850-5o Piso, Colonia Jardines del Bosque C.P.

44520, Guadalajara, Jalisco

+52 (33) 3188 4604 | [info.latam@apsystems.com](mailto:info.latam@apsystems.com)